






STATE	PROJECT	SHEET NUMBER
ST	PROJECT NUMBER PROJECT NAME	



NOTE:

1. Attach guardrail post to box culvert with 7/8-inch diameter high-strength threaded rods 8 1/2-inch in length with resin-bonded anchors. Use carbon steel rods with a minimum strength of 125 ksi and a minimum yield strength of 105 ksi. Rods, nuts, and washers have an electroplated zinc coating.
2. Wood blocks are shown. Blocks of an approved alternative may be used.
3. See Detail C617-32 for other details.



U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL HIGHWAY ADMINISTRATION
CENTRAL FEDERAL LANDS HIGHWAY DIVISION

CFLHD DETAIL
**MGS W-BEAM GUARDRAIL
STEEL POSTS
ATTACHED TO BOX CULVERT**

DETAIL APPROVED FOR USE 02/2019
REVISED: 09/2021

DETAIL
C617-38

Notes to the Designer

Updated September 2021

MGS W-Beam Guardrail Steel Posts Attached to Box Culvert

General Information

- All graphics and text will be in the sheet model.

- **Appropriate Applications.**

This drawing is used with box culverts with shallow fill.

Crash Test Criteria	MASH
Test Level	TL-3
FHWA Eligibility Letter	B-241
TF 13 Designator	SBW09c
Crash Test Report	TTI Report No. 405160-23-2



From TTI Report No. 405160-23-2

- **Limitations.**

Embankment over culvert ranges from 9" (min.) to 3' (max.).

- **Layout Guidance.**

See the FLH *Midwest Guardrail System FAQ* document for more information.

Applicable SCRs

- Section 563 (if weathering agent applied to galvanized elements)
- Section 617
- Section 710
- Section 725 (if weathering agent applied to galvanized elements)

Typical Pay Item Used

- 61701-4500 Guardrail system MGS, type 2, class A steel posts [LNFT] for galvanized steel
 - 61701-5100 Guardrail system MGS, type 4, class B steel posts [LNFT] for weathering steel
- Note: Use the same pay item as roadside rail.

Updates

- **February 2019**
 - New Detail drawing
- **April 2020**
 - Revised note 3, added note 4, minor CADD edits
- **September 2021**
 - Updated for OpenRoads Designer